

Connecting profiles system

Section	Photo	Specifications
		<p>PR SF003</p> <p>Profile 3 mm F-Shape, unpainted 6.1 m, 1.2 kg Profile is used for mounting of Composite Panels and 3 mm thick Sheet Materials</p>
		<p>PR SF004</p> <p>Profile 4 mm F-Shape, unpainted 6.1 m, 1.23 kg Profile is used for mounting of Composite Panels and 4 mm thick Sheet Materials</p>
		<p>PR SC003</p> <p>Profile 3 mm Angular, anode, matt silver, 6.1 m, 1.64 kg Profile is used for mounting and docking at 90° of Composite Panels and 3 mm thick Sheet Materials, as well as designing of Volumetric Shapes</p>
		<p>PR SH003</p> <p>Profile 3 mm H-Shape anode, matt silver, 6.1 m, 1.36 kg Profile is used for mounting and docking at 180° of Composite Panels and 3 mm thick Sheet Materials</p>
		<p>PR SH004</p> <p>Profile 4 mm H-Shape, unpainted 6.1 m, 1.61 kg Profile is used for mounting and docking at 180° of Composite Panels and 4 mm thick Sheet Materials</p>
		<p>ПPR SU003</p> <p>Profile 3 mm U-Shape anode, matt silver, 6.1 m, 0.72 kg Profile is used for framing of Composite Panels and 3 mm thick Sheet Materials</p>

